



RAFFA'S

BILTONG CABINETS

RAFFAS.CO.ZA



BILTONG CABINETS

FEATURES

- Well suited to small volume operations, hunters, home industries and biltong enthusiasts
- Preset temperature control to avoid tampering
- Heater cannot be switched on without the fan being in operation
- Efficient extraction fan for maximum air changes and uniform drying throughout the cabinet
- Unit can cure 25KG of wet product at a time
- Internal hanging brackets for improved flexibility
- High quality all S/Steel cabinet



JUNIOR - 245LT

BCB0245

SPECIFICATIONS

VOLTAGE	: 230V - 50Hz
POWER	: 0.75kW
DIMENSIONS	: 580 X 460 X 1080MM
WEIGHT	: 43KG
CHAMBER SIZE	: 500 X 450 X 910MM

Includes

10 S/Steel hanging rods
1 S/Steel drip tray

FEATURES

- The ideal machine for butcheries and supermarkets to produce high volumes of biltong
- Proven 20% performance benefit over competition
- Glass window for product display
- Unit fitted with anti-bacterial ultra violet lamp for product protection
- Locking door handle for security
- Adjustable thermostatic temperature control
- Powerful extraction fan to ensure maximum air changes for uniform drying throughout
- Heater cannot be switched on without the fan being in operation
- Unit can cure 100KG of wet product at a time
- High quality all S/Steel 1250LT cabinet



Do a dry cure (24 HR), or wet cure (12 HR) first with the temperature control switch off, and only the light and fan on. Then put the temperature control on setting 3, and leave for ± 3 days. The ideal temperature for drying biltong is 32°C - 34°C.

1250LT

BCB1250-R01

SPECIFICATIONS

VOLTAGE	: 230V - 50Hz
POWER	: 2 X 1.5kW
DIMENSIONS	: 1000 X 740 X 2015MM
WEIGHT	: 120KG
CHAMBER SIZE	: 950 X 730 X 1750MM

Includes

24 S/Steel hanging rods
1 S/Steel drip tray

Note

Optional additional extras available on request

