



RAFFA'S

HOSE REELS

RAFFAS.CO.ZA



HOSE REELS



10m STAINLESS STEEL

SPECIFICATIONS	
INLET	3/8" NPT female inlet
HOSE SIZE	3/8 x 35 in
HOSE LENGTH	10.7m
SPRAY VALVE	Front trigger water gun
SPRAY VALVE FLOW	15.5 L/min
PRESSURE RATING	20 to 125 psi
TEMP. RATING	4 to 93°C
ORDER CODE	TS/B-7132-05



10m EPOXY COATED

SPECIFICATIONS	
INLET	3/8" NPT female inlet
HOSE SIZE	3/8 x 35 in
HOSE LENGTH	10.7m
SPRAY VALVE	Front trigger water gun
SPRAY VALVE FLOW	15.5 L/min
PRESSURE RATING	20 to 125 psi
TEMP. RATING	4 to 93°C
ORDER CODE	TS/B-7232-05



15m EPOXY COATED
(ECONO MODEL)

SPECIFICATIONS	
INLET	3/8" NPT female inlet
HOSE SIZE	3/8 x 50 in
HOSE LENGTH	15.2m
SPRAY VALVE	Front trigger water gun
SPRAY VALVE FLOW	15.5 L/min
PRESSURE RATING	20 to 125 psi
TEMP. RATING	4 to 60°C
ORDER CODE	TS/5HR-242-12



UNIVERSAL SWING BRACKET
FOR HOSE REELS

DIMENSIONS	121 x 279 x 209mm
WEIGHT	3.5kg
FEATURES	
Designed for one person installation	
Easy Install stainless steel wall mount swing bracket	
Fits all T&S 3/8" and 1/2" hose reels	
Includes reel-to-bracket mounting hardware	
Positive stops built in to bracket to keep hose reel from hitting or damaging wall	
ORDER CODE	TS/G019430-45